![Vivitek logo - Vivid Color, Vivid Life]

Portable Projector

Vivitek DW350BD

WXGA projector with a brilliant image, multiple I/O ports and long-life lamp.

Features

- Brilliant WXGA (1,280 x 800) projection with a maximum WUXGA (1,920 x 1,200) resolution
- Bright 4,200 ANSI lumens of brightness for projection even in bright meeting rooms
- High 30,000:1 contrast ratio ensuring clear presentations and sharp text
- 1 way keystone adjustment support
- DLP® and BrilliantColor™ technologies for distinct and vibrant images
- Low cost of ownership and maintenance with an energy efficient lamp for up to 20,000 hours (Long Eco. Mode) of usage
- 6 segment (RYGCWB) color wheel for improved and vivid color reproduction
- Extensive connectivity inputs and outputs including HDMI v1.4b (x1), Composite Video, VGA-In (x1), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RS232, and USB 5V/1.5A(w/Service)
- Manual zoom and focus for easy adjustment and positioning flexibility
- Audio ready with 10 watt audio speaker and audio-in/out ports
- Quiet operation with low 29dB (Eco mode) acoustic noise
- Top sided lamp cover for simple lamp removal and insertion
- Environmentally friendly with less than 0.5W of power in stand-by mode
- Portable and lightweight at only 2.6kg (5.7lbs)
- Anti-theft security features include: Kensington® security slot, security bar, and power button lock

Specifications

Display Type	Single Chip 0.65" DLP Technology by TI
Brightness	4,200 Lumens
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	WUXGA (1,920 x 1,200)
Contrast Ratio	30,000:1 (Full On/Off)
Lamp Life/Type	5,500 hrs (Normal) 6,000 hrs (Long Eco) 20,000 hrs (Long Eco Mode) / 210W
Throw Ratio	1.55~1.86
Image Size (Diagonal)	40"~300"
Projection Distance	1.3~10.2m
Projection Lens	F#: F=2.42 – 2.62, f=22.5 – 25.79mm
Zoom Ratio	1.2x
Aspect Ratio	16:10
Offset	112.4%±5%
Keystone Correction	Vertical: ±40°
Horizontal Frequency	15 -102kHz
Vertical Frequency	23 - 120Hz
3D Compatibility	Yes
Speaker	10W
Computer Compatibility	VGA (640 x 480) to WUXGA (1920 x 1200)
Video Compatibility	NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
I/O Connection Ports	HDMI v1.4b (x1), Composite Video, VGA-In (x1), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RS232, USB 5V/1.5A (and Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Keypad Lock
Dimensions (WxDxH)	313 x 236 x 120mm (12.3" x 9.3" x 4.7")
Weight	2.6kg (5.7lbs)
Available Colors	White
Noise Level	32/29 dB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	250W (Normal Mode), 210W (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, Remote Control, Documentation Kit
Optional Accessories	Lamp

©2023 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.

![DLP Texas Instruments logo] ![BrilliantColor logo] ![DLP 3D Ready logo] ![HDMI logo]

Photos

A brand of ![Delta logo]